

## CURVE/SPOT LIGHT/TILTABLE/ANTI-GLARE

**Model: RR-DL3582**



### Feature:

- Anti-Glare
- Compact design
- Reflector in different beam angles

### Technical data:

▪ Light source	COB Chip, Citizen or others
▪ LED Power (max.)	9W (250mA@36V)
▪ System Power (ref.)	11W <small>(ref. only depends on the ECG)</small>
▪ Lumen flux (typ.)	700lm
▪ Colour temperature	2700K, 3000K, 4000K
▪ Colour rendering index	Ra≥90
▪ MacAdam Step	3
▪ Beam Angle	24D, 38D, 60D Reflector
▪ Tiltable	Yes
▪ Ingress protection	IP54
▪ Operation temperature	0-40C
▪ Protection Class	III
▪ LED Lifetime	50,000h L70B10
▪ Finishing	White RAL9016/Black RAL9005
▪ Construction	Aluminum, Polycarbonate
▪ Installation	Ceiling Recessed, spring type
▪ Dimension	85mm(OD)x 60mm(H)/Cutout 75mm
▪ LED Driver	Remote
▪ Trimless version	No

### Electronic control gear

NON-DIM/Dimmable


**IDP** MP series

1-10V/0-10V/DALI

**IDP** SC series

Other brand is available upon request

\*Use IDP multi-power LED Driver can trim down the output power according to actual application.



### LIGHT DISTRIBUTION for 3000K

wide 36.7°

h(m)	E(lx)	Ø(m)
1	1190	Ø0.66
2	297.5	Ø1.33
3	132.2	Ø1.99
4	74.38	Ø2.66
5	47.60	Ø3.32



**\*\*The specification is subject to change without note.\*\***